



## Model: AJE2427ZFZ (CAJ2440Z)

### Product Description

**Type:** Reciprocating  
**Application:** LBP - Low Back Pressure  
**Refrigerant:** R-404A  
**Voltage/Frequency:** 220-240V ~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
EN12900	230V ~ 50HZ	1225	309	359	499	2.45	.62	.72	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	-25°C (-13°F)	40°C (104°F)

#### General

**Evaporating Temp. Range:** -40°C to -12.2°C (-40°F to 10°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 22  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 21  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 782

#### Electrical

**Voltage Range (50 Hz):** 198-253  
**Voltage Range (60 Hz):** N/A  
**Locked Rotor Amps (LRA):** 27  
**Rated Load Amps (RLA 50 Hz):** 3  
**Rated Load Amps (RLA 60 Hz):** 0  
**Max. Continuous Current (MCC in Amps):** 5.7  
**Motor Resistance (Ohm) - Main:** 2.8  
**Motor Resistance (Ohm) - Start:** 11.6  
**Motor Type:** CSR  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

CCC Listed, CE Listed, GOST RUSSIA Listed, VDE Listed