



## Model: AJE4476YWZ (CAJ4476Y)

### Product Description

**Type:** Reciprocating  
**Application:** HBP - High Back Pressure  
**Refrigerant:** R-134a  
**Voltage/Frequency:** 220-230V ~ 60Hz 208-230V ~ 50Hz  
**Version:** N/A

### Product Specifications

#### Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power W	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W		Btu/Wh	kcal/Wh	W/W					
EN12900	230V ~ 60HZ	7263	1830	2128	873	8.32	2.1	2.44	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)
EN12900	220V ~ 50HZ	6123	1543	1794	695	8.81	2.22	2.58	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)

#### General

**Evaporating Temp. Range:** -15°C to 15°C (5°F to 59°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

#### Mechanical

**Weight:** 20  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 21.75  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 782

#### Electrical

**Voltage Range (50 Hz):** 187-242  
**Voltage Range (60 Hz):** 198-253  
**Locked Rotor Amps (LRA):** 26  
**Rated Load Amps (RLA 50 Hz):** 5.4  
**Rated Load Amps (RLA 60 Hz):** 5.2  
**Max. Continuous Current (MCC in Amps):** 8.5  
**Motor Resistance (Ohm) - Main:** 2.7  
**Motor Resistance (Ohm) - Start:** 13.6  
**Motor Type:** CSIR  
**Overload Type:** N/A  
**Relay Type:** N/A

#### Agency Approval

CE Listed, GOST RUSSIA Listed, NF Listed, VDE Listed