


Input data

Refrigerant	R449A	
Reference temperature	Dew point temperature	
Calculation mode	Refrigeration / Air Cond.	
Operating mode	Subcritical	
Power supply	400/3/50	
Condensing temperature	°C	45
Condensing pressure	bar	18,86
Liquid subcooling	K	0
Liquid temperature	°C	40,72
Evaporating temperature	°C	-10
Evaporating pressure	bar	3,61
Suction gas superheating	K	10
Useful fraction of superheating	%	100

Additional cooling required



Output data

Compressor :	V25-71Y	
Number of compressors :	FSx1	
Refrigerating capacity	kW	33,868
Refrigerating capacity [*ref]	kW	34,789
Evaporator capacity	kW	33,868
Power input	W	13956
Condenser capacity, theor.	kW	47,824
Current	A	28,28
COP/EER	W/W	2,43
Mass flow	kg/h	866
Operating frequency	Hz	50
Connection	-	PWS
Operating mode	-	100%
Discharge temperature	°C	82,83
Ratio (%)	%	100,0%
Note	-	
Oil flow	l/min	-
Heat Exchanged (oil Cooler)	kW	-
Oil Temp. at Oil Cooler Outlet	°C	-
Certified by	-	Frascold


Certified by:

- Frascold tentative data

Legend:

- *ref: At conditions according to EN12900
- Suction gas temperature = 20 °C
- Liquid subcooling = 0 K

P&I Diagram:



All data subject to change without notice

Model: V25-71Y

Refrigerant: R449A

Power supply: 400/3/50 PWS

Technical data:


Displacement	70,77 m³/h
Nominal compressor speed	1450 rpm
Motor voltage	400 V
Nominal operating frequency	50 Hz
Maximum allowed operating current (MRA)	43,5 A
Locked rotor current (LRA)	118,3 A
Locked rotor current (LRA), DOL	202,7 A
Number of pistons	4
Net weight	184 kg
Lubricant	FRASCOLD POE68
Oil charge	4 l
Maximum static pressure LP	20,5 bar
Maximum operating pressure HP	30 bar

Sound level:

Sound power level 5/50°C R404A @50Hz	77,5 dB(A)
Sound pressure (*) - Distance: 1 m	69,5 dB(A)
Sound power level -10/45°C R404A @50Hz	78 dB(A)
Sound pressure (*) - Distance: 1 m	70 dB(A)

*half sphere model

Motor connections:




All data subject to change without notice

Model: V25-71Y

Refrigerant: R449A

Power supply: 400/3/50 PWS

Dimensions:



Legend:

SV: Suction Valve	2 1/8" in - 54 mm	2: Low pressure connection	1/4" NPT
DV: Discharge valve	1 3/8" in - 35 mm	3: Oil charge plug	3/8" GAS
A: Length	703 mm	4: Oil level sight glass	-
B: Width	460 mm	5: Crankcase heater seat	-
C: Height	463 mm	6: Oil drain plug	1/4" GAS
D: Base mounting	381 mm	7: Liquid injection plug	1/4" NPT
E: Base mounting	305 mm	8: Liquid injection sensor plug	1/8" NPT
F: Suction Valve	133 mm	9: Oil pressure switch connection (LP)	1/4" NPT
G: Suction Valve	389 mm	10: Oil pressure switch connection (HP)	1/4" SAE
H: Suction Valve	130 mm	11: Oil filter	3/8" GAS
L: Discharge valve	152 mm	12: Oil return plug	1/4" NPT
M: Discharge valve	352 mm	14: Max discharge temperature sensor connection	1/8" NPT
N: Discharge valve	48 mm	15: Electronic oil pressure switch connection	3/4 UNF
1: High pressure connection	1/8" NPT	NP: Nameplate	

All data subject to change without notice

Model: V25-71Y

Refrigerant: R449A

Power supply: 400/3/50 PWS

Polynomial coefficients according to EN12900 for V25-71Y:

*S = T_{evap} ; D = T_{cond}

Reference conditions

Refrigerant	R449A
Ambient temperature	35 °C
Suction gas temperature	20 °C
Liquid subcooling	0 K
Frequency	50 Hz

	Refrigerating capacity [W]	Power input [W]
C1	8,753900E+004	3,065710E+003
C2	3,275850E+003	-2,107230E+002
C3	-6,431280E+002	4,353810E+002
C4	4,475340E+001	-5,987240E+000
C5	-2,372010E+001	1,098750E+001
C6	-3,554790E+000	-4,047920E+000
C7	2,227440E-001	-4,651850E-002
C8	-2,791630E-001	5,583250E-002
C9	-4,203530E-002	-3,997660E-002
C10	1,784630E-002	2,001380E-002

$$Y = C1 + C2*S + C3*D + C4*S^2 + C5*S*D + C6*D^2 + C7*S^3 + C8*D*S^2 + C9*S*D^2 + C10*D^3$$