


NEU6212GK



ENGINEERING CODE
958HA51

REFRIGERANT
R-404A

POWER SUPPLY
220-240 V 50 Hz

APPLICATION
MBP

MOTOR TYPE
CSIR

STANDARD
ASHRAE

COOLING CAPACITY
857 W

EFFICIENCY
1.7 W/W



DATA

GENERAL DATA

Model	NEU6212GK
Type	Hermetic Reciprocating
Technology	ON/OFF
Compressor Application	MBP
Expansion Device	Capillary Tube or Expansion Valve
Compressor Cooling	Fan/220
HP	1/2
Starting Torque	HST
Plant	SLOVAKIA

ELECTRICAL DATA

Start Winding Resistance	27.4 Ω at 25°C
Run Winding Resistance	4.87 Ω at 25°C
Locked Rotor Amperage (LRA) 50Hz	19 A
Rated Load Amperage (LMBP) at 50 Hz	3.5 A

MECHANICAL DATA

Displacement	8.77 cm ³
Oil Charge	350 ml
Oil Type	ESTER
Oil Viscosity	ISO22
Weight	10.6 Kg

ELECTRICAL COMPONENTS

Start Capacitor	53-64 µf/330 V
CSR CSIR BOX	No
Starting Device Type	RELAY
Overload Protection	T0964/G6

EXTERNAL CHARACTERISTICS

Base Plate	SMALL
------------	-------

Connector	Internal Diameter	Shape	Material
Suction	8.1 mm	SLANTED 42°	COPPER
Discharge	6.1 mm	STRAIGHT	COPPER
Process	6.1 mm	SLANTED 42°	COPPER

PERFORMANCE

TESTED CONDITIONS

Tested Refrigerant	R-404A
Tested Application	MBP
Tested Standard	ASHRAE
Tested Cooling	Fan
Tested Voltage	220 V
Tested Frequency	50 Hz
Refrigerant Temperature	Dew

RATED POINTS

Condensing Temperature °C	Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
54.4	-6.7	857	1.7	505	3.33	23.38

Test Condition: Subcooling 8.3 K, Return Gas 35 °C. Data generated in accordance to EN 12900:2013 polynomial equation and tolerance guidelines.

PERFORMANCE CURVE**Condensing Temperature 35°C**

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-20	676	1.92	352	2.87	14.67
-15	842	2.21	382	2.94	18.41
-10	1036	2.50	415	3.02	22.78
-5	1257	2.81	447	3.10	27.83
0	1506	3.18	473	3.19	33.63
5	1782	3.65	489	3.29	40.22
10	2087	4.26	490	3.40	47.67

Test Condition: Subcooling 8.3 K, Return Gas 35 °C. Data generated in accordance to EN 12900:2013 polynomial equation and tolerance guidelines.

PERFORMANCE CURVE**Condensing Temperature 45°C**

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-20	572	1.48	386	2.94	13.71
-15	719	1.72	417	3.03	17.35
-10	889	1.95	455	3.13	21.61
-5	1084	2.18	497	3.23	26.55
0	1303	2.42	538	3.35	32.22
5	1546	2.70	573	3.47	38.68
10	1814	3.03	599	3.61	45.98


Test Condition: Subcooling 8.3 K, Return Gas 35 °C. Data generated in accordance to EN 12900:2013 polynomial equation and tolerance guidelines.

PERFORMANCE CURVE**Condensing Temperature 55°C**

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-10	739	1.55	476	3.25	20.19
-5	906	1.73	522	3.39	24.99
0	1094	1.91	572	3.54	30.51
5	1303	2.10	621	3.70	36.81
10	1533	2.31	665	3.87	43.95

Test Condition: Subcooling 8.3 K, Return Gas 35 °C. Data generated in accordance to EN 12900:2013 polynomial equation and tolerance guidelines.

ENVELOPE



EXTERNAL DIMENSIONS

